



All Purpose Products

ALL PURPOSE **MaXimus**

Paintable Polymer Sealant

White Lightning® All Purpose MaXimus™ Paintable Polymer Sealant

combines performance characteristics of silicone and polyurethane, plus the paintability of a latex caulk in a solvent-free, non-yellowing formulation. Commonly applied at openings around doors, windows, trim, siding, countertops and many other projects.

- Premium paintability and adhesion
- Low odor
- Low VOC's*
- Superior durability
- Interior/exterior use

* Contains 1.0% VOC

Product Profile

Packaging:


All Purpose MaXimus™ Paintable Polymer Sealant	Color	Order #	UPC	Size
	White	WL9901775	0-23275-04169-1	10 FL OZ

25
YEARS


35
YEARS

40
YEARS

50
YEARS



Indoor / Outdoor
Use



Paintable

See opposite side
for technical information

ALL PURPOSE
MaXimus

PAINTABLE POLYMER SEALANT
FOR USE ON MOST PROJECTS

WHITE WHITE



All Purpose MaXimus™ Paintable Polymer Sealant

Physical Properties:

All Purpose MaXimus™ Paintable Polymer Sealant

Type:	All Purpose Polymer Sealant
Color:	White
Shelf Life:	12 Months
Full Cure Time:	24-48 Hours
Tack Free Time:	30 Minutes
Application Temperature:	55°F to 100°F
Service Temperature:	-50°F to 120°F
Mildew Resistance:	Resists Mildew Growth
Painting:	Paintable

Performance Data:

Joint Movement Capability:	Excellent
Joint Size:	1/2" x 1/2"
Freeze-Thaw Stability:	Avoid Repeated Freeze/Thaw While in Cartridge
Clean Up:	Citrus-Based Cleaner
Flexibility:	Excellent

Product Description:

White Lightning® All Purpose MaXimus™ Paintable Polymer Sealant is a hybrid sealant that can be painted. This premium technology combines performance characteristics of silicone and polyurethane, plus the paintability of a latex caulk in a solvent-free, non-yellowing formulation.

Basic Uses:

Commonly applied at openings around doors, windows, trim, siding, countertops and many other projects.

Surface Preparation:

Surface to be sealed should be clean, dry and free from oils, loose mortar, laitance, form release agents, old caulking, old paint, or other contaminants.

Painting:

MaXimus™ can be spray-painted immediately after application without hurting the bead of sealant. For best results, wait approximately 40 minutes or until bead is tack-free. MaXimus™ can be painted with a brush after 2 hours. Drytimes may be affected due to atmospheric conditions. Under moderate temperatures and humidity levels, product should reach full cure within 24-48 hours.

Cautions:

Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer contents to other containers for storage. In case of eye contact, flush with water. Get medical attention if irritation persists. If swallowed, get medical attention immediately. Protect from freezing.

Limitations:

Do not apply sealant at temperatures below 35°F. Do not use when rain is expected. Do not apply to frozen or frost covered surfaces, or to joints subject to heavy abrasion. Not for use below grade, on aquariums or for marine use below the water line.



For more information please call or write:

White Lightning® Products • 101 Prospect Ave. NW • Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com