



# All Purpose Products

## ALL PURPOSE **MEGALASTIC** Super Elastic Sealant

White Lightning® All Purpose MEGALASTIC Super Elastic Sealant is a premium sealant which *provides* "stretchability" of over 700% and has outstanding flexibility and adhesion to most surfaces. Ideal for any caulking project, it is commonly applied to doors, windows, trim, crown molding and any joints where extreme movement can be expected.

- Superior "Stretchability" of over 700%
- Superior adhesion
- No cracking
- Paintable
- Interior/exterior

### Product Profile


#### Packaging:

All Purpose MEGALASTIC Super Elastic Sealant	Color	Order #	UPC	Size	Case Pack
	White	WL0004001	0-23275-04506-4	10.1 FL OZ	12


ECONOMY

STANDARD

**PREMIUM  
LIFETIME**



Indoor / Outdoor  
Use



Paintable



Water Clean-up

See opposite side  
for technical information

Before using, carefully read  
CAUTIONS on back panel.

# All Purpose MEGALASTIC Super Elastic Sealant

## Physical Properties:

### All Purpose MEGALASTIC Elastic Sealant

Type:	Acrylic	Service Temperature:	-30°F to 180°F
Color:	White	Odor:	Low
Shelf Life:	24 Months	Shrinkage:	Low
Flash Point:	N/A (water based)	Vehicle:	Acrylic
Flammability:	N/A (water based)	Solids by Weight:	69.49
Full Cure Time:	48 hours	Weight/Gallon:	10.90
Tack Free Time:	2 hours		
Application Temperature:	Above 40°F		

## Performance Data:

Joint Size:	1/8" x 1/8" to 1/2" x 1/2"	Durability:	Excellent
Freeze-Thaw Stability:	Stable Through 5 Cycles	Mildew Resistance:	Resists Mildew Growth
Clean-Up:	Water	Water Resistance:	Excellent
Flexibility:	Superior	Painting:	Paintable

### Product Description:

White Lightning® All Purpose MEGALASTIC is a premium quality acrylic latex caulk ideal for interior and exterior applications.

### Surface Preparation:

Remove old caulk. Clean thoroughly to remove grease, dirt, oil, wax, loose paint, dust and soap film. Remove mildew with bleach and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

### Painting:

A minimum of 4 hours dry time is required before painting with latex or oil based paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

### Clean-Up:

Promptly clean tools and excess caulk with water or a damp cloth.

### Cautions:

Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer contents to other containers for storage.

### Limitations:

For best results, apply at temperatures above 40°F and allow 24 hours to cure before exposing to moisture. Do not apply to frozen or frost covered surfaces. Not for use below grade, on aquariums or for marine use below the water line.

### Specifications:

Exceeds performance requirements of Federal Specification TT-S-00230C Type II Class A and meets performance requirements of C-920 Class 35.



**For more information please call or write:**

White Lightning® Products • 101 Prospect Ave. NW • Cleveland, OH 44115  
1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service  
www.wlcaulk.com